

## CLAIMS

1. A commodity package, comprising a hanging member that has a hole for hanging, and a holding body for holding an article

characterized in that said holding body has: a housing portion including a first recess and a second recess for housing said article; a first brim portion and a second brim portion for closing said first recess and said second recess to form said housing portion; and a bending portion that connects said first recess and said second recess, and bends to fold back said holding body so that said first recess and said second recess are faced to each other,

said hanging member is interposed between said brim portions and said recesses,

said holding body has a first cutting portion for separating said first recess and the upper part of said first brim portion from each other, and a second cutting portion for separating said second recess and the upper part of said second brim portion from each other,

said hanging member has a third cutting portion for separating the upper part and the lower part thereof from each other, and

said first, second and third cutting portions are provided at different heights.

2. The commodity package in accordance with claim 1,

wherein said housing portion is formed on each side of the plane of said hanging member, said plane having said hole for hanging.

3. The commodity package in accordance with claim 1, wherein part of said first cutting portion and part of said second cutting portion are shaped such that said holding body forms a knob portion for opening and closing said commodity package after said cutting portions have been cut.

4. The commodity package in accordance with claim 1, wherein, in a portion where said hanging member is interposed between said first brim portion and said second brim portion, one of said brim portions has a projection for crushing and the other of said brim portions has a depression into which said projection is to fit, and said hanging member has a hole that accommodates said projection, such that said projection for crushing is put thorough said hole, said projection for pushing in the state of fitting into said depression is crushed, and a latch portion, formed as said projection for crushing transforms by extending outward, is latched into said hole and said depression to fix said hanging member to said holding body.

5. The commodity package in accordance with claim 1, wherein one of said first brim portion and said second brim portion has a depression and the other of said brim portions has a projection to fit into said depression.

6. The commodity package in accordance with claim 1,

wherein said holding body has a folding-back portion on each of the side rims thereof.

7. The commodity package in accordance with claim 1, wherein each of said first recess and said second recess has a depression on the right or the left side face of the inside thereof, and said hanging member has projections to fit into said depressions.

8. The commodity package in accordance with claim 1, wherein said bending portion comprises: a bottom portion that connects said first recess and said second recess; and a pair of line portions for folding capable of bending to fold back said holding body so that said recesses are faced to each other, said pair of line portions for folding being provided on boundary between said bottom portion and said recesses.

9. The commodity package in accordance with claim 8, wherein said holding body in which said housing portion is formed with said bottom portion can be placed vertically.